# Chapter E5 Management

Part E > General Controls for All Development

CHAPTER E5 APPROVED ON 27 APRIL 2015

AND COMMENCED ON 23 MAY 2015

Last amended on 20 January 2020

Repealed by with CP 2015 Amendment No. 5 on 1 December 2020

# Chapter E5 ▶ Waste Management

# Contents

CUI	tents
E5.1	INTRODUCTION
	E5.1.1 Background
	E5.1.2 Land to which this chapter applies
	E5.1.4 Objectives
	E5.1.5 Relationship to other parts of the DCP
E5.2	DEMOLITION AND CONSTRUCTION PHASE
E5.3	ON-SITE WASTE AND RECYCLING CONTROLS FOR ALL DEVELOPMENT
E5.4	DWELLING HOUSES, SEMI-DETACHED DWELLINGS AND DUAL OCCUPANCIES
E5.5	MULTI DWELLING HOUSING AND RESIDENTIAL FLAT BUILDINGS
E5.6	COMMERCIAL AND NON-RESIDENTIAL DEVELOPMENTS. O
E5.7	
	MIXED USE DEVELOPMENTS 12
	c.R
	IDCR V
	MDCR
	MDCP
\ \ \	ON MIDCIP
led led	ON MIDCIP
aled)	ON MIDCLE IN THE PROPERTY OF T
led	OAMDCB N
aled)	ON WIDCR P

Repealed by with CP 2015 Amendment No. 5 on 1 December 2020

\_\_\_\_\_

# E5.1 Introduction

# E5.1.1 Background

Waste and resource consumption is a major environmental issue and a priority for all levels of government within Australia. This is particularly the case as landfill sites become scarce and the environmental and economic costs of waste generation and disposal rise. Government and society alike are exposed to the issue of managing the increasingly large volumes of waste generated by society.

The building and construction industry in particular is a major contributor to waste, much of which is still deposited to landfill. Implementing effective waste minimisation strategies has the potential to significantly reduce these volumes as well as reduce costs. Well designed buildings that facilitate waste separation, recycling and composting support ongoing sustainability and recycling objectives.

This chapter identifies the on-site waste and recycling facilities that are to be included in the design of the development for its demolition, construction and ongoing use. It also identifies that a Site Waste Minimisation and Management Plan (SWMMP) is to be submitted with a development application (DA).

# E5.1.2 Land to which this chapter applies

This chapter applies to all land within the Wcollahra Municipality.

## E5.1.3 Development types that this chapter applies to

This chapter applies to development that requires development consent, including development involving demolition and construction.

## E5.1.4 Objectives

The objectives of this chapter are:

- O1 To assist applicants in planning for sustainable waste management, through the preparation of a site waste minimisation and management plan.
- To identify on-site requirements for waste and recycling storage and management, having regard to access and amenity.
- O3 To ensure waste management systems are compatible with collection services.
- To minimise noise and nuisance arising from waste and recycling collection having regard to the need to balance operational needs and functions of businesses with the amenity of nearby residential uses, particularly between 10pm and 7am.

## E5.1.5 Relationship to other parts of the DCP

This chapter is to be read in conjunction with the other parts of the DCP that are relevant to the development proposal, including:

- If located in a business centre—the controls in Part D: Business centres that apply to the land.

  Part F: Land Use Specific Controls this part contains chapters on Child Care Centres, Educational Establishments, Licensed Premises and Telecommunication. Decembr

# E5.1.6 Preparing your development application

### On-site waste and recycling facilities

All DAs are to address the provisions in Section 5.2 and 5.3 of this chapte

In addition, the following sections also apply to certain types of development:

- For dwelling houses, semi-detached dwellings and dual occupancies—refer to Section 5.4;
- For multi dwelling housing and residential flat buildings—refer to Section 5.5;
- For commercial and non-residential development-prier to Section 5.6; and
- For mixed use development—refer to Section

#### Site Waste Minimisation and Management Pla

The SWMMP outlines measures to minimise and manage waste generated during the demolition, construction, and ongoing use of the site.

The SWMMP identifies:

- volume and type of vaste and recyclables to be generated;
- storage and treatment of waste and recyclables on site;
- disposal of residual waste and recyclables;
- operational procedures for ongoing waste management once the development is complete;
- information to be shown on the DA plans.

Council's DA Guide contains a template for preparing the SWMMP. All information in the template is to be addressed.

Maximum waste minimisation and management benefits are achieved when the SWMMP is considered from the earliest stages of the development. It is for this reason that the SWMMP is generally required with the DA.

Council may allow an exception where both a DA and a construction certificate (CC) are required for a development. In such cases, a preliminary SWMMP may be required with the DA and the final SWMMP details relating to the demolition and construction phases must be submitted to Council for approval prior to the CC being issued.

,er 2020

\_\_\_\_\_

# E5.2 Demolition and construction phase

In the initial stages of development, attention to the design, estimating of materials and waste sensitive construction techniques and management practices, can achieve significant rewards in managing waste.

Demolition and construction activity should maximise resource recovery and minimise residual waste through waste avoidance, source separation and recycling. For example, applicants are encouraged to consider possible adaptive reuse of existing buildings, structures, and materials.

Obje	ctives	Conti	rols
01	To ensure that sustainable waste and recycling management is considered at the demolition and construction stages of development.	C1	A SWMMP is submitted with development application.  The SWMMP includes the following:  a) the estimater volume of waste generated: to be separately identified for the demolition, construction and ongoing operation phases of development;  b) the estimated volume of waste to be reused, recycled or disposed of; to be separately identified for the demolition, construction and ongoing operation phases of development;  c) how waste and recyclables will be stored and collected during the demolition and construction phases; and  d) measures for waste avoidance that have been incorporated into the design, material purchasing and construction techniques for the proposed development.
02	To maimise waste during the demolition of buildings or structures.		Development reuses or recycles salvaged materials onsite, where possible.  Development reuses or recycles excess
03	To encourage building design and	C4	construction materials, where possible.  Prefabricated components and recycled
	construction techniques that minimise waste generation.	C5	materials are used in the building, where possible.  Site disturbance and excavation is minimised.

# E5.3 On-site waste and recycling controls for all development

Waste and recycling facilities should be well designed and accessible to occupants and service providers, as the design affects use, amenity, and the movement and handling of waste for the life of the development.

Objectives	s		Controls
was mee tena	ensure that development provides te and recycling storage areas that et the waste and recycling needs of ants.		A SWMMP is submitted with the development application.  The SWMMP identifies the waste and recycling storage areas, by showing on the plans, the location and size of:  a) temporary indoor waste and recycling storage space for each dwelling or tenancy;  b) onsite waste and recycling storage areas;  c) individual and/or communal composting;  d) waste collection points;  e) garbage chutes and interim storage facilities for recyclable materials;  f) any service rooms (for accessing a garbage chute) on each floor of the building;  g) waste compaction equipment;  h) waste collection point for the collecting and emptying waste, recycling and garden waste bins; and  i) the path of travel for moving bins from the storage area to the collection point, where the collection is in a different location to the storage area. The width, height, grade and accessibility of the path of travel is to be identified.
	encourage source separation of te, reuse, and recycling materials.	C2	Waste and recycling storage areas are designed so recyclable materials are separated from general waste.

12025

# 03 To ensure that waste and recycle areas C3 Waste and recycling storage areas are located behind the building line or within are suitably designed and located and do non-habitable areas of the building. not cause nuisance or negative impacts. C4 Waste and recycling storage areas are integrated with the design of the overall development and do not detract from the streetscape. For example, external materials and finishes are a similar style and quality to the rest of the development. C5 Waste and recycling storage areas and composting areas are located so that the facility: a) is convenient and safely located for occupants to access; b) has an inobstructed access to the wasto and recycling collection point, Repealed by whoch 2015 Amendr xfree of steps and kerbs and does not have a grade more than 1:8; is secure and designed to minimise opportunities for vandalism; and d) does not reduce amenity for occupants of the site and adjoining properties, by way of visual, noise or olfactory impacts. Bulk bins, where permitted, are designed to be manually manoeuvred by one person in order to be serviced.

To ensure that waste and recycling collection points are suitably located in regards to safety and amenity.  C8 Bins may be collected from a kerb side location where site characteristics, number of bins and length of street frontage do not compromise safety.  C9 Where kerb side bin collection is not appropriate, bins are collected on site.  C10 Where a collection vehicle is required to enter a property, access di weways and internal roads are designed in accordance with Australian Standard 2890.2 Parking Facilities - Off-Street Commercial Vehicle Facilities - 2002.  C11 Waste and recycling collection points are located to allow collection vehicles to move in a continuous forward movement. Reversing should be avoided as it creates noise (from reverse beeping/alarms) and can also be less safe. If reversing is required the SWMMP accompanying the DA must justify why a continuous forward movement for collection cannot reasonably be accommodated.	collection points are suitably located in regards to safety and amenity.  C8 Bins may be collected from a kerb side location where site characteristics, number of bins and length of street frontage do not compromise safety.  C9 Where kerb side bin collection is not appropriate, bins are collected on site.  C10 Where a collection vehicle is required to enter a property, access driveways and internal roads are designed in accordance with A israilian Standard 2890.2 Parking Facilities - Off-Street Commercial Vehicle Facilities - 2002.  C11 Waste and recycling collection points are located to allow collection vehicles to move in a continuous forward in evement. Reversing should be avoided as it creates noise (from reverse beeping/alarms) and can also be less safe. If reversing is required the SWMMP accompanying the DA must justify why a continuous forward movement for collection cannot reasonably be accommodated.	collection points are suitably located in regards to safety and amenity.  C8 Bins may be collected from a kerb side location where site characteristics, number of bins and length of street frontage do not compromise safety.  C9 Where kerb side bin collection is not appropriate, bins are collected on site.  C10 Where a collection vehicle is required to enter a property, access driveways and internal roads are designed in accordance with Avsicalian Standard 2890.2 Parking Fac lities - Off-Street Commercial Vehicle Facilities - 2002.  C11 Waste and recycling collection points are located to allow collection vehicles to move in a continuous forward invenent. Reversing should be avoided as it creates noise (from reverse
location where site characteristics, number of bins and length of street frontage do not compromise safety.  C9 Where kerb side bin collection is not appropriate, bins are collected on site.  C10 Where a collection vehicle is required to enter a property, access driveways and internal roads are designed in accordance with Assiralian Standard 2890.2 Parking Facilities - Off-Street Commercial Vehicle Facilities - 2002.  C11 Waste and recycling collection points are located to allow collection vehicles to move in a continuous forward in vement. Reversing should be avoided as it creates noise (from reverse	location where site characteristics, number of bins and length of street frontage do not compromise safety.  C9 Where kerb side bin collection is not appropriate, bins are collected on site.  C10 Where a collection vehicle is required to enter a property, access driveways and internal roads are designed in accordance with A is calian Standard 2890.2 Parking Facilities - Off-Street Commercial Vehicle Facilities - 2002.  C11 Waste and recycling collection points are located to allow collection vehicles to move in a continuous forward in vement. Reversing should be avoided as it creates noise (from reverse beeping/alarms) and can also be less safe. If reversing is required the SWMMP accompanying the DA must justify why a continuous forward movement for collection cannot reasonably be accommodated.	location where site characteristics, number of bins and length of street frontage do not compromise safety.  C9 Where kerb side bin collection is not appropriate, bins are collected on site.  C10 Where a collection vehicle is required to enter a property, access driveways and internal roads are designed in accordance with Assicalian Standard 2890.2 Parking Facilities - Off-Street Commercial Vehicle Facilities - 2002.  C11 Waste and recycling collection points are located to allow collection vehicles to move in a continuous forward novement. Reversing should be avoided as it creates noise (from reverse beeping/alarms) and can also be less safe. If reversing is required the SWMMP accompanying the DA must justify why a continuous forward movement for collection cannot reasonably be accommodated.
appropriate, bins are collected on site.  C10 Where a collection vehicle is required to enter a property, access driveways and internal roads are designed in accordance with A stralian Standard 2890.2 Parking Fac lities - Off-Street Commercial Vehicle Facilities - 2002.  C11 Waste and recycling collection points are located to allow collection vehicles to move in a continuous forward in evenent. Reversing should be avoided as it creates noise (from reverse	appropriate, bins are collected on site.  C10 Where a collection vehicle is required to enter a property, access driveways and internal roads are designed in accordance with Aristralian Standard 2890.2 Parking Facilities - Off-Street Commercial Vehicle Facilities - 2002.  C11 Waste and recycling collection points are located to allow collection vehicles to move in a continuous forward movement. Reversing should be avoided as it creates noise (from reverse beeping/alarms) and can also be less safe. If reversing is required the SWMMP accompanying the DA must justify why a continuous forward movement for collection cannot reasonably be accommodated.	appropriate, bins are collected on site.  C10 Where a collection vehicle is required to enter a property, access driveways and internal roads are designed in accordance with Avistalian Standard 2890.2 Parking Facilities - Off-Street Commercial Vehicle Facilities - 2002.  C11 Waste and recycling collection points are located to allow collection vehicles to move in a continuous forward movement. Reversing should be avoided as it creates noise (from reverse beeping/alarms) and can also be less safe. If reversing is required the SWMMP accompanying the DA must justify why a continuous forward movement for collection cannot reasonably be accommodated.
enter a property, acce s driveways and internal roads are designed in accordance with Australian Standard 2890.2 Parking Facilities - Off-Street Commercial Vehicle Facilities - 2002.  C11 Waste and recycling collection points are located to allow collection vehicles to move in a continuous forward invement. Reversing should be avoided as it creates noise (from reverse	enter a property, access driveways and internal roads are designed in accordance with Avstralian Standard 2890.2 Parking Fac lities - Off-Street Commercial Vehicle Facilities - 2002.  C11 Waste and recycling collection points are located to allow collection vehicles to move in a continuous forward novement. Reversing should be avoided as it creates noise (from reverse beeping/alarms) and can also be less safe. If reversing is required the SWMMP accompanying the DA must justify why a continuous forward movement for collection cannot reasonably be accommodated.	enter a property, access driveways and internal roads are designed in accordance with Avs.calian Standard 2890.2 Parking Fac lities - Off-Street Commercial Vehicle Facilities - 2002.  C11 Waste and recycling collection points are located to allow collection vehicles to move in a continuous forward in vement. Reversing should be avoided as it creates noise (from reverse beeping/alarms) and can also be less safe. If reversing is required the SWMMP accompanying the DA must justify why a continuous forward movement for collection cannot reasonably be accommodated.
located to allow collection vehicles to move in a continuous forward movement. Reversing should be avoided as it creates noise (from reverse	located to allow collection vehicles to move in a continuous forward movement. Reversing should be avoided as it creates noise (from reverse beeping/alarms) and can also be less safe. If reversing is required the SWMMP accompanying the DA must justify why a continuous forward movement for collection cannot reasonably be accommodated.	located to allow collection vehicles to move in a continuous forward movement. Reversing should be avoided as it creates noise (from reverse beeping/alarms) and can also be less safe. If reversing is required the SWMMP accompanying the DA must justify why a continuous forward movement for collection cannot reasonably be accommodated.
	CV.	CV

#### E5.4 Dwelling houses, semi-detached dwellings and dual occupancies

•	nouses, semi-detached dwellings and du located waste areas, and must provide		upancies are to be designed with suitably tunities for recycling and composting.	20
conservati	e size of residential waste and recycling ion areas of Paddington and the West W those areas.	_	ge areas required in the heritage ara precinct, respond to the smaller lots	et 2020
Objective	es		Controls	, 
dw	promote reuse and recycling in velling houses, semi-detached vellings and dual occupancies.	C1	Each dwelling has an indoor waste and recycling storage space of sufficient size to accommodate at least one day's waste and recycling generation.	
		C2	Each dwelling has an onsite waste and recycling storage area either located externally behind the building line, or within a non-habitable area of the dwe!!in:	
		C3	For a dwelling located in an area other inan Paddington or West Woollahra, the size of the waste and recycling area accommodates:	
		<i>)</i>	a) 1 x 120L general waste bin;	
	a Mo		b) 1 x 240L green waste bin; and	
			c) 1 x 120L or 240L recycling bin.	
	S 2015 Amend	C4	For a dwelling located in Paddington or West Woollahra—the size of the waste and recycling area accommodates:	
	ack .		a) 1 x 120L general waste bin or 1 x 55L bin;	
			b) 1 x 120L or 55L green waste bin; and	
8	MOCK		c) 2 x 55L recycling crates or 1 x 120L recycling bin.	
69		C5	Each dwelling has an area suitable to accommodate on-site composting.	

# E5.5 Multi dwelling housing and residential flat buildings

The design of waste and recycling storage areas within the multi dwelling housing and residential flat buildings needs to address specific challenges with regard to waste volumes, ease of access and operation of waste sorting and removal systems.

Resources such as the *Better Practice Guide for Waste Management in Multi-Unit Dwellings* can also be used to inform design of medium density developments.

Obje	ectives		Controls
01	To promote reuse and recycling in multi dwelling housing and residential flat buildings.	C1	Each dwelling is provided with an indoor waste and recycling cupboard (or other appropriate storage space) for the interim storage of a millimum one day's garbage and recycling generation.
		C2	For residential flat building, a communal waste and recycling storage area for housing bins is provided.
		C3	For neural dwelling housing, a waste and recycling storage area is provided in the form of an area for each dwelling, or as communal waste and recycling storage area.
	Sell	C4	The size and design of the waste and recycling area or areas accommodate:
	Ebl.		<ul> <li>a) 120L of residual waste per residential dwelling;</li> </ul>
	201/2		<ul> <li>b) 55L of recyclables per residential dwelling stored in colour coded, shared use, 120L and/or 240L mobile garbage bins;</li> </ul>
	10CX		c) 240L shared use mobile garbage bins for food and garden organics.
`	oy MDCR 2015 Amen	C5	An area or areas suitable to accommodate on-site composting is provided. This may be for a communal facility or an area for each dwelling.
3		C6	Development containing 20 or more residential dwellings provides a garbage compaction unit.
		C7	Bulk waste bins are not encouraged and should only be considered for developments containing 12 or more dwellings.

# er 2020 02 To ensure that waste and recycling C8 Communal waste and recycling storage collection points are suitably located. rooms should generally be located in a basement location within the main building envelope. Where the storage room is in a separate standalone structure, the room and access to it is designed consistent with Crime Prevention Through Environmental Design (CPTED) principles. C9 Development containing four or more storeys provides a suitable system for the transportation of waste and recyclables from each storey to waste storage and collection areas, such as a garbage chute. This is in addition to the central waste storage area. Development containing 10 or more dwerlings provides a dedicated room or caged area for the temporary storage of discarded bulky items which are awaiting Repealed by MIDCR 2015 Amer removal. This storage area is readily accessible to all residents and located close to the main waste storage area. The travel distance between the waste and recycling storage area to the collection point is not more than 75 metres. For development assessed using State Environmental Planning Policy (Housing for Seniors or People with a Disability) 2004, the maximum distance is 50m. Collection and storage facilities are designed to provide an unobstructed and continuous accessible path of travel (as set out in the Australian Standard 1428 Design for Access and Mobility 2001) from the facility to: a) the entry of any adaptable housing; b) the principal entrance to each residential flat building; and c) the point at which bins are emptied and collected.

# E5.6 Commercial and non-residential developments

Developments containing a range of different non-residential uses present unique waste minimisation opportunities and management requirements. Flexibility in size and layout is often required to cater for the different needs of multiple tenants as well as future changes in use.

Noise from waste management activities needs to be managed where commercial uses are located near residential and other noise sensitive uses, particularly between 10pm and 7am. For example, noise when bins are emptied into collection vehicles, especially glass, and the reversing alarms of collection vehicles, can be particularly disturbing when these occur at noise sensitive times, such as late at night or in the early hours of the morning when most people are sleaving.

Obje	ectives		Controls
01	To promote reuse and recycling in mixed use development.	C1	A waste and recycling c upboard is provided for each individual kitchen area in the development, including kitchen
02	To ensure waste management systems are suitably located and readily accessible to occupants and service providers.	C2	areas in hotel rooms, motel rooms and staff food preparation areas.  Each waste and recycling cupboard is
03	To minimise nuisance and noise impacts on adjoining or nearby residential uses, from waste management associated with	~	designed to hold a minimum of one day's waste and keep general waste separated from recyclable materials.
	a pub, registered cub, or other type of licensed premises with a capacity of 100 or more patrops	<b>C.3</b>	A goods lift may be included in multiple storey buildings.
	from waste management associated with a pub, registered cub, or other type of licensed premises with a capacity of 100 or more patrons.	C4	The size of the waste and recycling storage area or areas is designed to accommodate the rates of waste generation and recyclable material generation identified in Table 1 below.
	all CR. L	C5	Bulk waste bins are not encouraged and should only be considered for developments containing 12 or more tenancies.
,	01/10	C6	Waste and recycling containers should be collected from a rear lane access point, where possible.
SO		C7	The SWMMP submitted with the development application must include:
			a) the location of glass and recycling collection and sorting areas, which are to be shown on the DA plans.  Note the installation of a glass crushing machine is encouraged to minimise noise from glass sorting.

Objectives	Controls
	b) the waste management operating procedures, including the collection times. These must minimise noise and disturbances to residential amenity, especially between 10pm and 7am.

# TABLE 1 Waste and recycling generation rates

Premises type	Waste generation	Recyclable material generation
Backpackers hotel	40L/occupant space/week	20L/occupant space./week
Boarding house, guest house	60L/occupant space/week	20L/occupant space/week
Food premises		, 0'
Butcher	80L/100m <sup>2</sup> of floor area/day	Variable
Delicatessen	80L/100m <sup>2</sup> of floor area/day	Variable
Fish shop	80L/100m <sup>2</sup> of floor area/day	Variable
Greengrocer	240L/100m <sup>2</sup> of floor area/Qay	80L/100m <sup>2</sup> of floor area/day
Restaurant/café	10L/1.5m²of floor ar€a nay	2L/1.5m <sup>2</sup> of floor area/day
Supermarket	240L/100m <sup>2</sup> of floor area/day	240L/100m <sup>2</sup> of floor area/day
Takeaway food shop	80L/100m <sup>2</sup> of floor area/day	Variable
Hairdresser, beauty salon	60L/occupant space/week	Variable
Hotel, licensed club, motel	5L(red space/day	1L/bed space/day
	50L/100m <sup>2</sup> of bar area/day	50L/100m <sup>2</sup> of bar area/day
-01	10L/1.5m <sup>2</sup> of dining area/day	50L/100m <sup>2</sup> of dining area/day
Offices	10L/100m <sup>2</sup> of floor area/day	10L/100m <sup>2</sup> of floor area/day
Shop up to 100m² floor area	50L/100m <sup>2</sup> of floor area/day	25L/100m <sup>2</sup> of floor area/day
Shop greater than Youm <sup>2</sup> floor area	50L/100m <sup>2</sup> of floor area/day	50L/100m <sup>2</sup> of floor area/day
Showroom	40L/100m <sup>2</sup> of floor area/day	10L/100m <sup>2</sup> of floor area/day

Source: We del Waste Chapter 2008 - Department of Environment and Climate Change

#### E5.7 Mixed use developments

	Controls
O1 To promote reuse and recycling in mixed use developments.	C1 The waste and recycling storage area for the residential component is separate to the waste storage area provided for the commercial component.
	C2 The controls in Section 5.5 (Multi dwelling housing and residential flat buildings) apply to use residential component of mixed use development.
	C3 The controls in Section 5.6 (Commercial and non residential developments) apply to the con-residential component of mixed use development.
ad by wide Range Ringer Range Ringer Range	